3D DISPLAY DEVICES WITH TRANSIENT LIGHT SCATTERING SHUTTERS

Cross Reference to Related Application

This claims the benefit of United States
Provisional Application No. 60/256,382, filed
December 18, 2000.

Background of the Invention

The present invention relates to three-dimensional (3D) display devices having liquid crystal
shutters that can change very quickly from optically
transparent to strongly light scattering and vice
versa.

Liquid crystal shutters are electro-optic
devices that are electrically switchable between a
transparent state and a light scattering state by
varying an electric field. Such shutters can be made
from a variety of liquid crystalline preparations.
Often, these liquid crystal preparations are stabilized
in a polymer matrix. The polymer network formed by the
matrix improves the electro-optic performance of light
scattering shutters by stabilizing the texture of the
liquid crystal. This aids in the return of the liquid
crystal molecular orientation to the desired stable
configuration and reduces the switching time between
transparent and scattering states.

Polymer stabilized liquid crystal (PSLC) cells preferably used in liquid crystal shutters can be prepared by mechanically entrapping the liquid crystals in the micropores of a plastic or glass sheet or by evaporation of water from a polymer emulsion containing liquid crystals.

More commonly, PSLC cells are made by preparing a mixture of synthetic monomer, photoinitiator, and liquid crystal and then photopolymerizing the preparation. Prior to photopolymerization, the homogeneous mixture of liquid crystal and monomer is placed between glass cell walls spaced about 10 microns apart. The solution is then exposed to ultraviolet light to form a film. As the film forms, the liquid crystals undergo a phase separation from the polymer. Polymer dispersed liquid crystals (PDLCs) made according to this method include dispersions of sub-micron sized droplets of liquid crystal in a polymer matrix. In the absence of an electric field, the directors of the liquid crystal are randomly oriented. The directors of the liquid crystal are the preferred molecular orientations of the liquid crystal mesophase, which can range from very ordered to very disordered (e.g., randomly oriented). When the directors are randomly oriented, the PDLCs appear light scattering and transmit little light. The refractive index of the polymer is chosen to match as closely as possible the refractive index of the liquid crystal such that upon application of an electric field, refractive index discontinuities are eliminated and the shutter becomes transparent. PDLCs having high polymer concentrations (> ~20 wt-%), however, display a hazy appearance at oblique incident angles even when the

electric field is on. At large enough viewing angles,
the perceived mismatch between the effective index of
refraction of the liquid crystal and the refractive
index of the polymer makes the film appear essentially
5   opaque.

To provide wider viewing angles, smaller
percentages of polymer can be used with cholesteric or
chiral nematic liquid crystals. When the electric
field is off ("field-off state"), the polymer disrupts
10   the long range order of the liquid crystals, thus
creating refractive index discontinuities and a light
scattering appearance. Application of the electric
field causes the liquid crystal directors to
homeotropically align with the electric field (i.e.,
15   the long axis of the liquid crystals aligns
perpendicular to the cell wall). This eliminates the
refractive index discontinuities and makes the liquid
crystal polymer film transparent. In both high and low
percentage polymer films, the addition of a polymer to
20   the liquid crystal gives rise to shutters that scatter
light in the absence of an electric field.

PSLCs, however, have a number of
disadvantages. The monomer/photoinitiator combination
used to form the PSLC cells exists in a metastable
25   state that is maintained only through careful handling.
Unwanted exposure to heat and light, for example, can
cause premature polymerization that ruins the shutter.
The extra processing steps and careful handling needed
to prepare polymer-based light scattering shutters can
30   dramatically increase costs and reduce manufacturing
yield.

Multistable liquid crystal shutters (also
referred to as liquid crystal displays or LCDs) can be

prepared without the need for polymers, thus avoiding
their additional manufacturing costs (see, e.g., United
States Patent No. 5,453,863). However, LCDs operated
according to the '863 patent also have shortcomings
5   that limit the effectiveness of the displays at
shuttering light from transient events, such as those
associated with pulsed lasers or photographic flash
lamps. According to the '863 patent, a sufficiently
low electric field pulse applied to the device
10 described therein results in a light scattering state
that is milky-white in appearance, corresponding to a
focal conic texture. This focal conic texture, though,
permits transmission of a significant portion of
incident light at the cell gap typically employed in
15 LCDs. Moreover, if an electric field high enough to
homeotropically align the liquid crystal is applied,
the focal conic texture will only form if the electric
field is turned off slowly. Thus, the focal conic
texture is not an effective texture to shutter fast
20 transient events.

        Furthermore, if the electric field is removed
quickly, LCDs of the '863 patent relax to a planar
reflecting texture. The planar reflecting texture
reflects light at a maximum wavelength corresponding to
25 $\lambda = np$, where λ is the wavelength, n is the average
refractive index of the liquid crystalline material
($n = (n_e + n_o)/2$ where n_e is the extraordinary
refractive index and n_o is the ordinary refractive
index), and p is the pitch (which is the distance
30 required for the director of a chiral liquid crystal to
rotate 360 degrees). The time required for the liquid
crystal to reconfigure from a homeotropic texture to a
planar texture can be several seconds, which for many

applications is too slow. Although surfactants, such
as those described in United States Patent
No. 5,661,533, have been developed to improve the
transition time, they typically do not address the
limited spectral reflectivity of the liquid crystal in
cases where blocking across a broad spectral range
(e.g., the visible spectrum) is important.

A liquid crystal shutter that can switch very
quickly between a transparent state and a strongly
light scattering state (which scatters light across a
broad visible spectral range) would be advantageous in
a number of different applications, including 3D
multiplanar volumetric display systems (i.e., systems
in which images actually occupy a definite volume of
three-dimensional space).

Many known 3D display systems
disadvantageously require specialized eyewear or
headgear such as goggles, helmets, or both. Such
eyewear is often bulky and uncomfortable and can cause
eye fatigue. Furthermore, this eyewear reduces the
perception of viewing an actual 3D image.

A known 3D volumetric display system reflects
light from a laser source off of a rapidly spinning
multifaceted mirror onto a rapidly spinning projection
screen. Such rapidly spinning components, however, can
be relatively large and thus need to be carefully
balanced to avoid vibration and possibly catastrophic
failure. Additionally, the size, shape, and
orientation of 3D volume elements (i.e., voxels) within
the display depends on their location from the shaft
that rotates the mirrors, resulting in display
resolution that is dependent on the position of the
viewer.

Other types of 3D volumetric display systems, such as multiview autostereoscopic displays, are also known. Such multiview autostereoscopic displays, however, do not display a field of view that is
5 continuous in all directions as the viewer moves with respect to the display device.

In view of the foregoing, it would be desirable to provide 3D display devices that have high resolution/voxel count.

10 It would also be desirable to provide 3D display devices that do not have the mechanical and optical limitations of known devices described above.

It would further be desirable to provide 3D display devices that include a liquid crystal shutter
15 that can switch very quickly between a transparent state and a strongly light scattering state.

Summary of the Invention

It is an object of this invention to provide 3D display devices that have high resolution/voxel
20 count.

It is also an object of this invention to provide 3D display devices that do not have the mechanical and optical limitations of known devices described above.

25 It is further an object of this invention to provide 3D display devices that include a liquid crystal shutter that can switch very quickly between a transparent state and a strongly light scattering state.

30 In accordance with the invention, transient light scattering shutters based on chiral liquid crystals are provided. The shutters switch very

quickly between a highly transparent state and a very low transparent, highly scattering state. The shutters are optically clear when an electric field across the shutters is on ("field-on state") and are scattering in the field-off state. When the electric field is quickly turned off, the shutters become strongly scattering (transmission < 1%) for a fraction of a second before relaxing to a weakly scattering static state.

The invention also provides multi-planar volumetric displays that include a plurality of such transient light scattering shutters. These displays scatter light off of the plurality of shutters at preferably a video rate to generate 3D images. A multi-surface optical display device formed with the plurality of transient light scattering shutters advantageously provides for natural viewing, with substantially all of the depth cues associated with viewing a real object. This minimizes eye strain and permits viewing for extended periods of time without fatigue or bulky and uncomfortable eyewear or headgear.

Brief Description of the Drawings

The above and other objects and advantages of the invention will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

FIG. 1 illustrates cross-sectionally an embodiment of a liquid crystal cell of a transient light scattering shutter according to the invention;

FIG. 2 illustrates a multi-planar volumetric display system according to the invention;

FIGS. 3(a)-3(b) illustrate graphically as a function of time the relationship between voltage and the transparent and scattering states of an embodiment of a transient light scattering shutter according to the invention;

FIGS. 4-6 illustrate graphically the transparency of an embodiment of a transient light scattering shutter as a function of voltage according to the invention;

FIGS. 7-10 illustrate successive displays of images that form a volumetric three-dimensional image on transient light scattering shutters according to the invention.

Detailed Description of the Invention

The following terms and definitions are used herein:

"Chiral liquid crystal" refers to liquid crystals that have a chiral mesophase.

"Infrared" refers to radiation in the electromagnetic spectrum having a wavelength from about 700 nanometers to about 10 microns.

"Near-infrared" refers to radiation in the electromagnetic spectrum having a wavelength from about 700 nanometers to about 2.5 microns.

"Ultraviolet" or "UV" refers to radiation in the electromagnetic spectrum beyond the violet end of the visible spectrum, having a wavelength from about 4 to about 400 nanometers.

"Visible spectrum" refers to radiation in the electromagnetic spectrum that is visible to the human

eye. The visible spectrum has a wavelength from about 400 nanometers to about 700 nanometers.

"Transient light scattering state" refers to an unstable, highly light scattering, liquid crystal texture formed by removing an electric field that causes the light scattering shutters of the invention to be transparent to incident light. The transient light scattering state is composed of microdomain textures, which are randomly oriented with respect to each other, and give rise to the highly light scattering appearance of the liquid crystalline material. Application of an electric field ends the transient light scattering state and erases the opacity of the liquid crystalline material.

The transmission percentage of a spectrum of light is given in terms of the total number of photons transmitted within the specified spectral range, not with respect to every wavelength within the spectral range.

FIG. 1 shows a liquid crystal cell 2 of a light scattering shutter in accordance with the invention. Cell 2 includes two glass or plastic cell walls 1 and 3 whose inner surfaces are coated with a series of layers that include the following: transparent conducting layers 9 and 11; insulating layers 13 and 15; cell seals 17 and 19; spacers or alignment layers 21, 23, and 25; and a liquid crystalline light modulating material layer 27, which is preferably not polymer stabilized. In a particular embodiment, the liquid crystalline material is substantially polymer free. Insulating layers 13 and 15 prevent short circuits and are composed of, for example, silicon oxide. Cell seals 17 and 19 maintain

cell integrity and enable vacuum filling. These seals
can be composed of, for example, thermally cured epoxy.

Cell 2 preferably further includes barrier
layers 5 and 7. Barrier layers 5 and 7 prevent
5   migration of impurities from the glass into the
transparent conductor and are composed of, for example,
silicon oxide. Optional additional layers may include,
for example, inorganic oxides such as hafnium oxide or
magnesium dioxide, which can improve the cell's light
10 transmission. Optional surface layers also can be
applied to the cell to affect the liquid crystal
directors or to alter the contrast, reflection, or
switching characteristics of the cell. These optional
surface layers may be rubbed, unrubbed, or otherwise
15 untextured.

In general, the materials composing the cell
layers should have appropriate refractive indices and
thicknesses to minimize reflective losses within the
cell.

20 Cell walls 1 and 3 can be any suitable glass
or plastic substrate. The substrate material is chosen
such that it has an index of refraction preferably
matched to the underlying layers of the cell such that
reflection and refraction of light are minimized. The
25 exterior surfaces of cell walls 1 and 3 are preferably
treated with anti-reflection (AR) layers, such as
laminated films, solgel dip coatings, or evaporated
dielectric oxides to further improve light
transmission. The interior surfaces of the cell walls
30 are also preferably treated with an index matching
layer to minimize refractive index mismatch between the
cell walls and adjacent layers. Additionally, or
alternatively, the cell walls can be treated with a

layer that limits selected wavelengths of light to
alter the performance of the light scattering shutter.
Moreover, a layer that limits light from, for example,
the ultraviolet spectrum, may improve the stability of
5   the light scattering shutter. In another embodiment,
the cell walls have embedded within them one or more
substances that absorb selected wavelengths of light.

Conducting layers 9 and 11 can be any
suitable transparent conductive material that results
10   in a uniformly applied electric field to the liquid
crystal mixture. Typical conductors include, for
example, indium tin oxide (ITO), other metallic oxides,
or possibly organic conductors. These transparent
conductive layers can be applied to the glass or
15   plastic substrate by any suitable commercial method,
such as evaporation or sputtering.

A refractive index difference between
conducting layers 9 and 11 and cell walls 1 and 3 may
produce unwanted reflections at the interfaces thereof.
20   To reduce those unwanted reflections, additional layers
of AR material may be optionally disposed on cell
walls 1 and 3. For example, an AR layer having an
optical thickness of about one quarter of a typical
wavelength of light, such as about 76 nm, and having a

25   refractive index approximately equal to $\sqrt{n_1 \times n_2}$ (where
n_1 is the refractive index of the substrate and n_2 is
the refractive index of the conducting layer) can
reduce the reflection at the substrate-conductive layer
interface to very low levels. In particular
30   embodiments, MgF_2 or solgel may be used to form the AR
layer.

A voltage source 29 (e.g., from MVD
controller 31 of FIG. 2) generates an electric field

via conducting layers 9 and 11 between the cell walls
of optical element 36 (FIG. 2). This causes the liquid
crystals in liquid crystalline mixture 27 to align and
transmit light 62 through optical element 36 with
5   little or no scattering. Optical element 36 is thus
substantially transparent. In one embodiment, optical
element 36 in its transparent state preferably
transmits greater than about 85% of the incident light
from the visible spectrum.

10   Electrical conductors 60 and 61 are connected
to transparent conducting layers 9 and 11 at the edges
of the cell where layers 9 and 11 are exposed.
Connections can be made via a number of techniques
including but not limited to conducting epoxy, metallic
15 tape with conducting adhesive, solder, organic
conductors, or anisotropic conductors.

           The optical scattering of the liquid
crystalline material in a shutter of the invention is
controlled by an electric field provided by voltage
20 source 29, which is preferably capable of reversing its
polarity. Apparently, the electric field untwists the
chiral nematic or cholesteric liquid crystal molecules
and homeotropically aligns the liquid crystal directors
to transform the liquid crystals into a transparent
25 state (denoted "T" in FIG. 3(b)). When the voltage is
turned off, the liquid crystalline material forms
microdomain textures (denoted "S" in FIG. 3(b)), which
have a size on the same order of magnitude as the
scattered light wavelength. Although the directors
30 within each microdomain are ordered (i.e., short range
order), they are disordered with respect to other
microdomains (i.e., no long range disorder). This
localized chiral domain formation is believed to

contribute to the observed transient shuttering effect
in light scattering shutters of the invention, as
illustrated in FIGS. 3(b) and 4-6. During the
transient light scattering state, the shutter of the
5 invention strongly scatters incident light. In
particular embodiments, the shutter preferably
transmits less than about 1% of the incident light from
the visible spectrum. More preferably, the transient
light scattering state transmits less than about 0.5%
10 of the incident light from the visible spectrum. In a
more preferred embodiment, the shutter of the invention
transmits less than about 0.1% of the incident light
from the visible spectrum during the transient light
scattering state. In another embodiment, the transient
15 light scattering state scatters light from one or more
of the following spectral ranges: the visible spectrum,
the ultraviolet spectrum, the near-infrared spectrum,
and the infrared spectrum.

The transient light scattering state is not
20 stable when the electric field is off. After the
voltage is turned off, the microdomains gradually
coalesce, forming an equilibrium structure that is only
weakly scattering (denoted "S*" in FIG. 3(b)). This
diffuse light scattering texture permits transmission
25 of a significant portion of the incident light.

If the voltage is turned on, however, the
liquid crystalline material becomes transparent again.
Preferably, when the voltage is turned back on, the
voltage polarity is reversed. In one embodiment, the
30 liquid crystalline material preferably transmits
greater than 85% of the incident light each time it
becomes transparent.

The planar reflecting texture (i.e., the "reflective state") of the invention preferably reflects wavelengths outside the spectral range scattered by the transient light scattering state. The reflected wavelength of the liquid crystalline material while in the reflective state can be selected by appropriate adjustment of the pitch and refractive indices of the substances that compose the liquid crystalline material. In one embodiment, the selected reflected wavelength is preferably outside the visible region of the electromagnetic spectrum. If the pitch is selected, for example, such that the liquid crystalline material maximally reflects light wavelengths outside the visible spectrum, the liquid crystalline material in its reflective state will appear colorless and transmissive. In another embodiment of the invention, the selected maximum reflected wavelength is shorter than the visible spectrum (e.g., in the ultraviolet wavelength range). In a further embodiment, the selected reflected maximum wavelength is in the near-infrared range. In a more preferred embodiment, the selected maximum wavelength is between about 850 nanometers and about 1.4 microns.

Light modulating liquid crystalline material 27 preferably comprises a mixture of nematic liquid crystal having positive dielectric anisotropy and a chiral dopant in an amount sufficient to produce a desired pitch length. In another embodiment, light modulating liquid crystalline material 27 comprises cholesteric liquid crystals. The shuttering effect is expected to occur in some or all chiral liquid crystal mesophases, including for example smectic C* ferroelectric liquid crystals. Suitable chiral

nematic, cholesteric, or smectic chiral textured liquid crystals are commercially available. The needed amount of liquid crystal and chiral dopant varies depending on the particular liquid crystal and chiral dopant used.

5   Chiral dopant induces or enhances the helical twist of the liquid crystal molecules in the liquid crystalline mixture. As discussed in United States Patent No. 6,217,792, incorporated herein by reference, the pitch of the liquid crystalline material

10 is approximately inversely proportional to the concentration of the chiral dopant $(p = (1/HTP)(1/c))$, where c is the concentration of the chiral dopant and HTP is a proportionality factor representative of the helical twisting power (HTP) of the chiral dopant.

15 Thus, the desired pitch can be obtained by selecting a chiral dopant with suitable helical twisting power or by controlling the concentration of the dopant in the liquid crystalline mixture, or both. The chiral dopant may be, for example, a cholesteric liquid crystal

20 either alone or in combination with other chiral dopants.

           In a preferred embodiment, when the voltage is turned on beyond a certain threshold, the liquid crystalline material switches to a transparent state.

25 While reversing the polarity of voltage source 29, the liquid crystalline material goes through a transient state, which strongly scatters light, before becoming transparent again as a result of the reversed-polarity electric field. As shown in FIGS. 3(a) and 4-5, the

30 transient state becomes the most scattering when the voltage is approximately zero. FIG. 4 illustrates the transmission of light as a function of time using a triangular waveform with a 132-volt peak at 20 Hz.

FIG. 5 illustrates the transmission of light with a truncated triangular waveform. In one embodiment, the electric field is preferably applied by an AC voltage with rms amplitude greater than or equal to the
5   threshold voltage of the transient light shutter. More preferably, a DC bipolar voltage is applied to the shutter. In another embodiment, a unipolar voltage is applied to the shutter.

The threshold voltage needed to turn the
10   transient shutter transparent depends on the liquid crystalline material and the thickness of the gap between the cell walls of the transient shutter. Typically, at least 10 volts per micron of spacing between the inner surfaces of the cell walls is needed
15   to reach the threshold voltage.

The applied voltage can be any suitable waveform in which the voltage drops to zero to induce the aforementioned transient state. The waveform can be, for example, sinusoidal, triangular, truncated
20   triangular, or square. Most preferably, the voltage reverses polarity each time after it drops to zero. The maximum frequency at which the voltage can be turned on and off to switch between transparent and transient scattering states is limited by the material
25   response of the liquid crystalline material. This is easily determined by those of ordinary skill in the art.

Spacers or alignment layers 21, 23, and 25 (FIG. 1) separate the transparent electrodes.
30   The spacers are preferably chemically inert, transparent, substantially insulating, and maintain a uniform cell gap. They are preferably made of glass or polymers in the shape of, for example, beads or rods.

If made of polymer, the material can be, for example, cellulose acetate, cellulose triacetate, cellulose acetate butyrate, polyurethane elastomers, polyethylene, polycarbonates, polyvinylfluoride,
5 polytetrafluorethylene, polyethylene terephthalate, polybutylene terephthalate, or mixtures thereof. Alternatively, polymer blends or co-extruded polymers can be used to make the spacers. The spacers define the thickness of liquid crystalline material 27 in
10 cell 2 and are preferably in the range of about 4 to about 20 microns thick. More preferably, the spacers are about 10 to about 15 microns thick.

In some shutters according to the invention, transition speeds between the transparent and
15 scattering states appear to vary with shutter temperature. For example, heating the shutter (using nematic liquid crystal and ZLI-4572 chiral additive) from about 29° C to about 65° C reduces the transition time from the transparent state to the scattering state
20 from about 1.56 msec to about 0.34 msec, and reduces the transition time back to the transparent state from about 2.73 msec to about 0.45 msec. A reduction in viscosity of the liquid crystal is believed to contribute to the decreased transition times. In one
25 embodiment, the conducting layer, made from ITO for example, is slightly resistive, and can be used to heat the liquid crystalline material. This embodiment has the advantage of providing intimate contact between the heater and liquid crystalline material as well as
30 uniform spatial heating of the liquid crystalline material.

Switching speeds may also be influenced by or controlled with additives in the liquid crystal layer.

For example, the additives described in WIPO
Publication WO 98/53028 of Kent Displays, Inc., are
expected to lower viscosity and reduce switching times.
Other known additives, such as surfactants, should
5   provide similar effects.

By using voltage source 29 synchronized to an
external device such as a laser, video projector,
photographic flash lamps, strobe light, etc., the
transient light scattering shutter can shutter or
10 reflect light for video rate displays, 3D volumetric
displays, ultrafast optical shutters, etc. As
described in United States Patent No. 6,100,862,
incorporated herein by reference, a plurality of
individual transient light scattering shutters may be
15 combined to form a multi-surface optical device that
can be integrated into a multiplanar volumetric display
(MVD) system. Each transient light scattering shutter
functions as an individual optical element of the
multi-surface optical device. Multiplanar optical
20 element (MOE) device 32 (FIG. 2) converts a series of
two-dimensional images from image projector 63 into a
3D volume image.

In such a multi-surface optical system, an
optical element controller controls the optical
25 translucency of the liquid crystal elements, such that
a single liquid crystal element is in an opaque light-
scattering state in order to receive and display an
image from the image projector. The other remaining
liquid crystal elements are in their transparent state.
30 The optical element controller successively causes each
liquid crystal element to be in the opaque light-
scattering state in order to receive and display a
respective image, thus generating a volumetric 3D image

with 3D depth. To have the set of images appear as one
continuous image, the optical element controller, in
one embodiment, rasters through successive liquid
crystal elements at a high rate, at least that of a
5 standard video rate (e.g., 30 Hz or faster).

The optical element controller is preferably
a waveform generator. In one embodiment, the optical
element controller is a bipolar waveform generator.
FIG. 6 shows an example of the transparency of a
10 shutter as a function of voltage 604 when operated with
a bipolar waveform generator. In one embodiment using
the bipolar waveform generator, the first transparent
conducting layer of the transient light scattering
shutter is held at zero volts while the second
15 transparent conducting layer is brought to a positive
voltage sufficient to cause the shutter to become
transparent. To transform the shutter to a transient
light scattering state, the voltage is removed from the
second transparent conducting layer and held at zero
20 volts for a period of time, typically about 2
milliseconds. The voltage on the second transparent
conducting layer is then reversed to a negative voltage
sufficient to cause the shutter to become transparent.
During the next scattering cycle, the voltage on the
25 second transparent conducting layer is again brought to
zero volts and held before returning to a positive
voltage. Operated in this manner, the average voltage
applied to the cell is zero.

In an alternative embodiment using a bipolar
30 waveform generator, the voltage applied to the cell is
positive. The first transparent conducting layer is
held at zero volts while the second transparent
conducting layer is brought to a positive voltage

sufficient to cause the shutter to become transparent.
To transform the shutter into the transient light
scattering state, the voltage on the first transparent
conducting layer is increased until equal to the
5 voltage on the second conducting layer such that the
voltage difference across the shutter is zero. To
return the shutter to transparency again, the voltage
on the second conducting layer is brought to zero
volts, resulting in a reversal of the polarity of the
10 electric field applied to the shutter. To cause the
shutter to become scattering a second time, the voltage
on the first conducting layer is brought to zero volts,
resulting in a zero electric field across the shutter.
To return the shutter to transparency once more, the
15 voltage on the second conducting layer is brought back
to a positive voltage. Again, the average voltage
applied to the cell is zero. This alternative
embodiment advantageously requires only a single
voltage supply and applies an identical square voltage
20 waveform to each side of the shutter. Furthermore, the
duration of the transient light scattering state can be
advantageously controlled, within the limits of the
liquid crystalline material microdomain lifetime, by
controlling the time delay between applications of
25 voltage to each side of the conducting layer.

In another embodiment, the optical element
controller is a unipolar waveform generator that
operates as follows: the first transparent conducting
layer of the transient shutter is held at zero volts
30 while the second transparent conducting layer is
brought to a positive voltage sufficient to cause the
shutter to become transparent. To transform the cell
into a transient light scattering state, the voltage is

removed from the second transparent conducting layer
and held at zero volts for a period of time, typically
about 2 milliseconds. To return the cell to the
transparent state, the voltage on the second
5 transparent conducting layer is returned to the
original positive voltage.

        FIG. 2 shows a multiplanar volumetric display
(MVD) system 10 that generates 3D volumetric images in
accordance with the invention. That is, the 3D images
10 occupy a definite and limited volume of 3D space, and
thus exist at the location where the images appear.
Such 3D images are true 3D, as opposed to an image
perceived to be 3D because of an optical illusion
created by, for example, stereographic methods.

15   Three-dimensional images generated by MVD
system 10 preferably have very high resolution and are
displayed in a large range of colors. The 3D images
therefore have the characteristics associated with
viewing a real object. For example, such 3D images may
20 have both horizontal and vertical motion parallax or
lookaround, allowing a viewer 65 to move and yet still
receive visual cues that maintain the 3D appearance of
the images.

        Advantageously, a viewer 65 needs no eyewear
25 such as stereographic visors or glasses to view the 3D
image. Furthermore, the 3D image has a continuous
field of view both horizontally and vertically, with
the horizontal field of view equal to about 360° in
certain display configurations. Additionally, the
30 viewer can be at any arbitrary viewing distance from
MVD system 10 without loss of 3D perception.

        The image to be viewed in three dimensions is
converted by MVD controller 31 into a series of

two-dimensional image slices each at a particular depth
through the 3D image. The frame data corresponding to
the image slices are then rapidly output from the high
speed image buffer of MVD controller 31 to image
5 projector 63.

Prior to transmission of the image data to
image projector 63, MVD controller 31, or alternatively
graphics data source 16, preferably performs 3D
anti-aliasing on the image data to smooth the features
10 of displayed 3D image 34. This reduces or eliminates
any jagged lines in depth between, for example,
parallel planes aligned orthogonal to a z-axis. Such
jagged lines result from display pixelization caused by
the inherently discrete voxel construction of MOE
15 device 32 with optical elements 36, 38, 40, and 42,
which are aligned in x-y planes normal to a z-axis. As
data corresponding to image slices 24, 26, 28, and 30
are generated, an image element may appear near an edge
of a plane transition (e.g., optical elements 36
20 and 38). To avoid a jagged transition at a specific
image element, slices 24 and 26, for example, are both
preferably generated such that each of respective
images 44 and 46 includes the specific image element.
Thus, the image element is shared between both planes
25 formed by optical elements 36 and 38, which softens the
transition and allows 3D image 34 to appear more
continuous. The brightness of an image element on
consecutive optical elements is varied in accordance
with the location of the image element in the image
30 data.

Image projector 63 has optics 67 for
projecting two-dimensional slices 24, 26, 28, and 30 of
a 3D image at a high frame rate and in a time

sequential manner to MOE device 32. The two-dimensional slices are projected to generate a first volumetric 3D image 34, which appears to viewer 65 to be present within the space of MOE device 32. MOE

5 device 32 includes a plurality of optical elements 36, 38, 40, and 42 which, under the control of MVD controller 31, receive respective slices 24, 26, 28, and 30, which are displayed as two-dimensional images 44, 46, 48, and 50. During each frame rate

10 cycle, one optical element receives and displays a respective slice. The number of slices generated by MVD controller 31 is equal to the number of optical elements. That is, each optical element represents a unit of depth resolution of a generated and displayed

15 volumetric 3D image.

The overall display of each of slices 24, 26, 28, and 30 on respective optical elements 36, 38, 40, and 42 occurs at a sufficiently high frame rate (e.g., rates preferably greater than about 35 Hz) such that

20 viewer 65 perceives a single continuous volumetric 3D image 34, and not a series of individual two-dimensional images. Thus, for example, images 44, 46, 48, and 50 may each be a different cross-section of a sphere, and the generated image will appear as a

25 single 3D sphere to viewer 65. This image can be advantageously viewed directly without a stereographic headset or any other equipment needed by the viewer.

In alternative embodiments, images 44, 46, 48, and 50 can be generated such that an overall image

30 has a mixed 2D and 3D appearance, such as, for example, 2D text below a 3D sphere. An application of this 3D display with a 2D backdrop may be a graphical user interface (GUI) control pad. The GUI control pad would

appear to viewer 65 to comprise a 2D virtual flat
screen GUI, such as that provided by Microsoft
Windows®, and 3D graphical elements appearing on that
virtual flat screen display.

5   Volumetric 3D image 34 is viewable within a
range of orientations. Furthermore, emitted light 52
from MOE device 32 is preferably further processed in
accordance with this invention by a "real" image
projector 54 to generate volumetric 3D image 56.

10 Image 56 appears to be substantially the same image as
volumetric 3D image 34, but floating in space at a
distance from MOE device 32. Real image projector 54,
or alternatively a floating image projector, can be a
set of optics, such as mirrors and lenses, for

15 collecting light 52 emitted from MOE device 32 and for
re-imaging 3D image 34 out into free space. Real image
projector 54 is preferably a high definition volumetric
display (HDVD), which includes a conventional spherical
or parabolic mirror to produce a signal viewing zone

20 located on an optical axis of MOE device 32. For
example, real image projection systems can be the
apparatus described in United States Patents
Nos. 5,552,934 and 5,572,375, each of which is
incorporated herein by reference.

25   Because both volumetric 3D images 34 and 56
appear to viewer 65 to have volume and depth, and
optionally also color, MVD display system 10 can be
adapted for virtual reality and haptic/tactile
applications, such as teaching surgery (see the example

30 below). Real image projector 54 allows floating 3D
image 56 to be directly accessible for virtual
interaction. MVD system 10 preferably includes a user
feedback device 58 that receives hand movements from

viewer 65 using a hand-held device (e.g., forceps) to attempt to manipulate either of images 34 and 56. Such hand movements are translated by user feedback device 58 into control signals that are conveyed via

5 interface 14 to MVD controller 31. MVD controller 31 responds by modifying one or both of images 34 and 56 to appear as if responding to the movements of viewer 65.

Another application of MVD system 10 includes

10 a force feedback interface that can be used as a surgical simulator and trainer. In such a simulator, a user can see and feel 3D virtual anatomy, such as an animated beating heart and its reactions to virtual prodding by the user. This simulator could be used to

15 obtain certification as a surgeon, practice innovative new procedures, or even perform remote surgery over the Internet, for example, using Internet communication protocols. Tactile effects may thus be combined with animation to provide real-time simulation and

20 interaction with users of 3D images generated by MVD system 10.

In another embodiment, MOE device 32 includes a stack of glass transient light scattering shutters as optical elements, which are separated by either glass,

25 plastic, liquid, or air inter-stack spacers. Alternatively, the optical elements may be plastic or other substances having various advantages, such as lightweight construction. The inter-stack spacers are preferably combined with the cell walls in an optically

30 continuous configuration to eliminate reflections at internal interfaces. The cell walls and spacers of the liquid crystal display can be optically combined by either optical contact, index matching fluid, or

optical cement. Alternatively, the inter-stack spacers
can be replaced by liquid such as water, mineral oil,
or index matching fluid. Such liquids can be
circulated through an external chilling device to cool
5   MOE device 32. Also, such inter-stack liquid-spaced
shutters may be transported and installed empty to
reduce their overall weight. The spacing liquid can
then be added after installation.

The spacing distance between optical elements
10   may be constant, or alternatively may be variable such
that the depth of MOE device 32 is greatly increased
without increasing the number of optical elements. For
example, because viewer 65 loses depth perception with
increased viewing distance, the optical elements
15   positioned farther from viewer 65 may be spaced farther
apart. For example, logarithmic spacing may be used,
in which the spacing between optical elements increases
with distance from viewer 65. This advantageously
enables one to create a physically deeper display
20   without the need to use more optical elements at
increasing distance from the viewer.

If AR layers are used, the spacing material
between optical elements may be removed to leave air or
a vacuum between each element, thus reducing the
25   overall weight of MOE device 32. Such AR layers may be
vacuum deposited, evaporated, or sputtered.
Alternatively, the AR layers may be applied by spin
coating, dip coating, or meniscus coating with solgel.

In another embodiment of the invention, only
30   one optical element of MOE device 32 is in the highly
scattering state at any given time. As image
projector 63 projects slices 24, 26, 28, and 30 at a
high rate through a projection cycle, with one slice

emitted per cycle, the scattering plane is rapidly
rastered through the depth of MOE device 32 to form an
effectively variable depth projection screen. The
remaining transparent optical elements permit viewer 65
5 to see the displayed image from received image
slices 24, 26, 28, and 30.

        As shown in FIGS. 7-10, successive frame data
is fed from MVD controller 31 to image projector 63 to
generate images 82, 84, 86, and 88. In one embodiment
10 of the invention, images 82, 84, 86, and 88 are
displayed sequentially. Any changes that are sought in
the 3D image are made by sequentially refreshing all of
the optical elements in MOE device 32. Such sequential
frame ordering may be sufficient in marginal frame rate
15 conditions, such as frame rate displays of about 32 Hz
for still images and of about 45 Hz for images
displaying motion.

        MVD controller 31 synchronizes the switching
of optical elements 36, 38, 40, and 42 such that
20 optical element 36 is opaque as image 82 is emitted
thereon (FIG. 7), optical element 38 is opaque as
image 84 is emitted thereon (FIG. 8), optical
element 40 is opaque as image 86 is emitted thereon
(FIG. 9), and optical element 42 is opaque as image 88
25 is emitted thereon (FIG. 10). MVD controller 31
preferably introduces a delay between feeding each set
of frame data (i.e., the image data that together form
the 3D image) to image projector 63 and causing a given
optical element to be opaque such that image
30 projector 63 has enough time during the delay to
generate respective images 82, 84, 86, and 88 from the
sets of frame data.

While one optical element is opaque and displays a respective image thereon, the remaining optical elements are transparent. Thus, image 82 on optical element 36 (FIG. 7) is visible through at least
5 optical element 38. Similarly, image 84 (FIG. 8) is visible through at least optical element 40, and image 86 (FIG. 9) is visible through at least optical element 42. Because images 82, 84, 86, and 88 are displayed at a high rate by image projector 63 onto
10 respective optical elements 36, 38, 40, and 42, which are switched between opaque and transparent states at a high rate, images 82, 84, 86, and 88 appear as a single volumetric 3D image 34.

To form a continuous volumetric 3D image 34
15 without perceivable flicker, each optical element 36, 38, 40, and 42 receives a respective image and is switched to an opaque state preferably at a frame rate greater than about 35 Hz. Accordingly, to refresh and update the entire 3D image, the frame rate of image
20 projector 63 should be greater than about N x 35 Hz, where N is the number of optical elements in MOE device 32. For a stack of 50 transient light scattering shutters forming MOE device 32, each having an individual optical element frame rate of 40 Hz, the
25 overall frame rate of image projector 63 should be greater than about 50 x 40 Hz = 2000 Hz. High performance and high quality volumetric 3D imaging by MVD system 10 may require frame rates on the order of 15 kHz.

30 In another embodiment, changes to the 3D image may be made by refreshing the optical elements of MOE device 32 in a semi-random order to lower image jitter and to reduce motion artifacts. Each optical

element is still only updated once each time the MOE
device displays all the slices composing the 3D image.
Such semi-random plane ordering includes multi-planar
interlacing in which even numbered planes are
5   illuminated with images, and then odd numbered planes
are illuminated with images. This increases the
perceived volume rate without increasing the frame rate
of image projector 63.

     MOE device 32 maintains the image resolution
10 originally generated in image projector 63 to provide
high fidelity 3D images. Liquid crystal optical
elements 36, 38, 40, and 42 are haze-free in the
transparent state and switch rapidly between the
transparent state and the opaque, scattering state.
15 Moreover, the scattering state efficiently and
substantially scatters light from image projector 63 to
form an image.

     In a preferred embodiment, the liquid crystal
shutter is planar and rectangular but, alternatively,
20 it can be curved or have other shapes, such as
cylindrical. For example, cylindrical liquid crystal
shutters can be fabricated by techniques such as
extrusion and may be nested within each other.

     Most of the panel's volume and weight are
25 associated with the glass substrates, which contribute
to a potentially bulky and heavy MOE device 32,
particularly as the transverse size and number of
panels increase. Liquid crystal panels made of plastic
is one way to decrease weight. Very thin plastic
30 substrates, for example, can be fabricated continuously
and at very low cost by a roll-to-roll process. By
using such thin plastic, MOE device 32 may also be

collapsible when not in operation. This advantageously
allows MVD system 10 to be portable.

Optical elements 36, 38, 40, and 42 may also
include other inorganic materials in addition to or
5 instead of liquid crystal technology, such as an ITO
layer organically applied by spin or dip coating.

In an embodiment of the invention, MOE
device 32 includes 10 liquid crystal panels and is
preferably about 5.5 inches (14 cm) long by about 5.25
10 inches (13.3 cm) wide by about 2 inches (4.8 cm) in
depth. Image projector 63 includes an acousto-optical
laser-beam scanner that has a pair of ion lasers to
produce red, green, and blue light, which is modulated
and then scanned by high frequency sound waves. The
15 laser scanner is capable of vector scanning 166,000
points per second at a resolution of 200 x 200 points.
When combined with the 10-panel MOE device 32 operating
at 40 Hz, MVD system 10 produces 3D images with a total
of 400,000 voxels. A color depth of 24-bit RGB
20 resolution can be obtained, with an image update rate
of preferably about 1 Hz. Using real image projector
54, a field of view of about 100° x 45° (horizontal x
vertical) can be attained.

In another embodiment, MOE device 32 includes
25 12 liquid crystal panels and is preferably about 6
inches (15.2 cm) long by about 6 inches (15.2 cm) wide
by about 3 inches (7.7 cm) in depth. In this
embodiment, image projector 63 includes a pair of Texas
Instruments® video projectors, designed to operate in
30 field-sequential color mode to produce grayscale images
at a frame rate of about 180 Hz. By interlacing the
two projectors, a "single" projector is effectively
formed with a frame rate of about 360 Hz. This

produces 12-plane volumetric images at a rate of about
30 Hz. The transverse resolution attainable is 640 x
480 points. When combined with this 12-plane MOE
device 32 operating at about 30 Hz, MVD system 10
5   produces gray 3D images with a total of 3,686,400
voxels. A color depth of 8-bit grayscale resolution is
obtained with an image update rate of about 10 Hz.
Using real image projector 54, a field of view of about
100° x 45° can be attained.

10   In a further embodiment, MOE device 32
includes 50 liquid crystal panels and is preferably
about 15 inches (38.1 cm) long by about 13 inches (33.0
cm) wide by about 10 inches (25.4 cm) in depth. When
combined with this 50-plane MOE device 32 operating at
15   about 40 Hz, MVD system 10 produces 3D images with a
total of 13,107,200 voxels. A color depth of 24-bit
RGB resolution is obtained, with an image update rate
of about 10 Hz. Using real image projector 54, a field
of view of about 100° x 45° can be attained. With such
20   resolution and a non-interlaced volume rate of 40 Hz,
MVD system 10 advantageously has a display capability
equivalent to a conventional monitor with a 20-inch
(50.8 cm.) diagonal.

        In a still further embodiment, optical
25   elements of the invention have a transverse resolution
of 1280 x 1024 and a depth resolution of 256 planes.
The system preferably operates in a depth interlaced
mode in which alternate panels are updated at about
75 Hz, with the complete volume refreshed at a rate of
30   about 37.5 Hz. Such interlacing provides a higher
effective volume rate without having to increase the
frame rate of image projector 63.

In yet another embodiment, MOE device 32 includes 500 liquid crystal panels and is preferably about 33 inches (84 cm) long by about 25 inches (64 cm) wide by about 25 inches (64 cm) in depth. The liquid crystal panels preferably have a depth resolution and a transverse resolution of 2048 x 2048 pixels, which could produce 3D images with greater than 2 billion voxels. With such resolution and size of display, the MOE device 32 in this embodiment has a display capability equivalent to a conventional monitor with a 41-inch (104 cm) diagonal.

MVD system 10 advantageously controls and produces occlusion, which is the obstruction of light from background objects by foreground objects. A limited form of occlusion, called computational occlusion, can be produced by picking a particular point of view and then simply not drawing surfaces that cannot be seen from that point of view. This improves the rate of image construction and display. When viewer 65 attempts to look around foreground objects, however, the parts of background objects that were not drawn are not visible. In an embodiment of the invention, MVD system 10 compensates for the lack of occlusion by interspersing optical elements in a scattering state to create occlusion by absorbing background light. In another embodiment, guest-host PDLCs may be interspersed within the array of transient light scattering shutters to create and control occlusions. In guest-host PDLCs, a dye is mixed with the liquid crystal molecules. The appearance of the dye in the PDLC can be masked or made to appear depending on whether the liquid crystalline material is transparent.

MVD system 10 advantageously exhibits little or no contrast degradation caused by ambient illumination. Real image projector 54 and MOE device 32 are preferably enclosed in a housing that

5 reduces the amount of ambient light reaching MOE device 32, thus preventing contrast degradation.

Alternatively, contrast degradation can be reduced in accordance with the invention by increasing the illumination from image projector 63 in proportion

10 to the ambient illumination and by installing an absorbing plastic enclosure around MOE device 32 to reduce the image brightness to viewable levels. The ambient light must pass through the absorbing enclosure twice to reach viewer 65 -- once on the way in and

15 again after scattering off the optical elements of MOE device 32. In contrast, the light from image projector 63, which forms the images, only passes through the absorbing enclosure once on the way to viewer 65, and thus has a lower loss of illumination.

20 In another embodiment of the invention, the chiral nematic liquid crystal mixture consists of 72% by weight nematic liquid crystal E44 (Merck) and 28% by weight cholesteric liquid crystal CB 15 (Merck). This mixture is placed in a 14-micron thick cell with a

25 silicon oxide barrier and insulator layer and no alignment layer. The static transmission of the cell is about 20.7% at a wavelength of about 632.8 nm.

FIG. 4 shows the amount of light transmission 402 of such a cell at 632.8 nm when driven

30 by a triangular wave 404 with a peak voltage of 132 volts at a frequency of 20 Hz. The cell has periods of high transparency with light transmission of approximately 90%. This is comparable to the 92% light

transmission expected of ordinary glass without AR
layers. The cell also has periods of very low
transparency with transmission less than 0.1%. The
duration of the low transmission period is determined
5 by the rate at which the drive voltage decreases to
zero volts.

Truncated triangular wave 504 of FIG. 5
allows adjustment of both the repetition rate and the
duration of the low transmission period. The rate can
10 be controlled by adjusting the periodicity of the
waveform, while the duration can be controlled by
manipulating the slope of the voltage drop to zero.
The maximum period of time that the shutters of the
invention can maintain a desired low transmission
15 percentage is limited by the length of time that the
transient microdomains in the shutters persist. If a
very low transmission percentage is required (i.e.,
high opacity), as many microdomains as possible should
be in the shutters. However, even in that case,
20 duration of the very low transmission percentage will
be very short (e.g., 2-10 ms), because of the short-
lived nature of the microdomains. Thus, decreasing the
voltage over a long period of time may not be effective
in sustaining that very low transmission level.
25 Alternatively, if a higher low transmission percentage
is acceptable, fewer microdomains are needed to scatter
light. Thus, in that case, a slower decaying voltage
will prolong the duration of that low transmission
percentage.

30 Another embodiment of the invention combines
95% by weight nematic liquid crystal E44 (Merck) and 5%
by weight chiral additive ZLI-4572 (Merck). This
mixture is placed in a cell with a 14-micron cell gap

and no alignment layers. The resulting transient
shutter has a static light transmission of about 3.8%
and a transient light transmission of about 0.04% when
driven to the scattering state by triangular
5 waveform 504. The light transmission of the
transparent state is about 86.4%.

　　　　　Thus it is seen that transient light
scattering shutters and 3D volumetric display systems
using such shutters are presented. One will appreciate
10 that the present invention can be practiced by other
than the described embodiments, which are presented for
purposes of illustration and not of limitation.
Numerous modifications and substitutions can be made
without departing from the spirit of the invention.
15 For example, instead of using planar optical elements
such as flat panel liquid crystal display shutters,
curved optical elements can be used in a manner as set
forth above. Accordingly, the present invention is
limited only by the claims which follow.